

## PRODUCT PECIFICATIONS

# SXV-9 SERIES

9 Year – Interior/Exterior CAST PVC WINDOW FILM

### CONSTRUCTION

#### Face Film

2 mil cast vinyl

#### Adhesive Release

Clear, permanent pressure sensitive

### Installation

Installation should be in accordance with manufacturer's installation instructions. Installed using the same methods for installing window films.

### Warranty

This SOLYX® product will be free from defects in material and manufacture for a period of nine (9) years from the date of installation. See Warranty information for specific details.

### PHYSICAL PROPERTIES

#### Outdoor Durability

9 years when properly processed and applied (Vertical exposure, unprinted film).

#### Minimum Surface/Ambient Air Application Temperature

50° F. to 90° F. (10° C to 32°C)

#### Service Temperature Range

-40° F. to +225° F. (-40° C. to +107° C.) -Reasonable range of temperatures, which would be expected under normal environmental time and temperature conditions.

#### Typical Film Caliper (w/adhesive)

2.5 – 3.5 mils

#### Chemical Resistance

Resists mild acids, alkalis, and salts.

#### Water Resistance

Excellent water resistance

NOTE: Always pretest your specific substrates prior to actual application.

### Adhesion

Substrate	24 hrs.
Acrylic	7 lb/in. (1.2 kg/cm)
Alodine Aluminum	9 lb/in (1.6 kg/cm)
Auto BC/CC	5 lb/in (0.9 kg/cm)
Fruehauf Prepainted Panels	6 lb/in (1.1 kg/cm)
Polycarbonate	6 lb/in (1.1 kg/cm)
Polypropylene	3 lb/in (0.5 kg/cm)

#### Shelf Life

2 years when stored in a clean, dry area, out of the direct sunlight, and at less that 100° F.

**Exterior Installation:** This film is suitable for exterior applications. Expected outdoor life is 9 years

**Size:** Standard Rolls 48" (some 60" ) wide x 150 ft