

SOLYX® Glass Finishes

SX-1309 Fine Crystal Frost



Manufacturer Detail

SOLYX® SX-1309 Fine Crystal Frost film is recommended for application to interior and exterior glass (inside surface). Manufactured from a durable PVC with a decorative embossed surface, perfect for privacy, decorative or architectural applications. Total nominal thickness is between 3 and 4 mil. Supplied with a silicone liner, which protects the clear, pressure-sensitive adhesive, and applied using the same tools and techniques for window films.

Fire Rating

Flammability Rating applied to Glass or Plastic Sheet surfaces:
Horizontal Burn (Flame Spread) ASTM D-635 inch Less than 1.0
UL 94 Rating UL 94, Classification V-O
Class A 0 -25 Flame Spread Index 0 -450

Fire & Explosion Hazard

Product will burn. Under normal conditions it is not an explosion hazard.
Hazardous Products of Combustion May Form: carbon dioxide, carbon monoxide, hydrogen chloride, and dense smoke or irritation vapors.
Flash Point (TCC): NA
Explosive Limits: NA
Auto ignition Temperature: NA
Extinguishing Media: regular foam, carbon dioxide, dry chemical or water spray
Fire Fighting Instructions: Wear a self-contained breathing apparatus with a full face piece operated in the positive pressure demand mode.

Product Description

SOLYX® SX-1309 Fine Crystal Frost is a clear translucent, high grade embossed vinyl film designed to simulate sandblasted glass. It is perfect for privacy, decorative or architectural applications. Ideal for obscuring visibility while allowing excellent light transmission.

Specifications

Product Code	SX-1309
Product Family	Simple Frosted
Film Type	Vinyl
Adhesive Type	Pressure-sensitive
Usage	Interior or Exterior
Available Width(s)	60" (1524mm)
Full Roll Length	100 linear feet (30.5m)
Thickness	3-4 mil
Visible Light Transmission	72%
UV Transmission	30%
Infra-Red Transmission	80%

Product Construction

Face Film
3-4 mil Vinyl

Adhesive
Clear, Pressure-sensitive

Release Liner
Silicone

Installation and Warranty

Installation

Installation should be in accordance with manufacturer's installation instructions.

Warranty

This SOLYX® product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. Exterior applications have a three (3) warranty. See warranty information for specific details.

Product Distribution and Contact Information

Distribution

SOLYX® Decorative Films are available through qualified Installing Dealers, Distributors or from Decorative Films, LLC.

Samples submitted upon request.

Contact Information

Decorative Films, LLC
1-888-657-5224
www.decorativefilm.com

Product Details