

SOLYX® Glass Finishes

SX-9000 Clear Waters



SOLYX: SX-9000
Clear Waters

Product Details

SOLYX® SX-9000 Clear Waters Decorative Privacy Glass Film is recommended for application to interior glass and exterior glass as well as Plexiglas or Polycarbonate sheets. This film is a durable vinyl with a decorative embossed pattern, 4 mil thickness with a silicone liner and pressure-sensitive adhesive. It is perfect for privacy, decorative or architectural applications. The pattern direction is down the length of the roll

Fire Rating

When applied to glass or plastic surfaces:
 Horizontal Burn (Flame Spread) ASTM D-635 inch Less than 1.0
 UL 94 Rating UL Classification V-0
 Class A 0 -25 Flame Spread Index 0 -450

Installation and Warranty

Installation

Installation should be in accordance with manufacturer's installation instructions.

Warranty

This SOLYX® product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Distribution and Contact Information

Distribution

SOLYX® **Decorative Films** are available through qualified Installing Dealers, Distributors or from Decorative Films, LLC.

Samples submitted upon request.

Contact Information

Decorative Films, LLC
 1-888-657-5224
www.decorativefilm.com

Product Description

SOLYX® SX-9000 Clear Waters is a clear translucent, high grade embossed textured pattern vinyl film. This product is ideal for obscuring direct visibility while allowing excellent light transmission.

Specifications

Product Code	SX-9000
Product Family	Textured
Film Type	Vinyl
Adhesive Type	Pressure-sensitive
Usage	Interior or Exterior
Available Width(s)	60" (1524mm)
Full Roll Length	100 linear feet (30.5m)
Thickness	4 mil
Shading Coefficient	.93%
Visible Light Reflection	8%
Visible Light Transmission	51%
UV Transmission	56%
Solar Heat Reflection	7%
Solar Heat Transmission	76%
Infra-Red Transmission	63%

Product Construction

Face Film

4 mil vinyl

Adhesive

Clear, Pressure-sensitive – 0.7 – 0.87 mil

Release Liner

1.5 mil Silicone