

SOLYX® Glass Finishes

SXHK-01 Shoji Screen



SOLYX® SXHK-01 Shoji Screen film is recommended for application to interior and exterior glass (inside surface). Made of durable Polyester fiber and PVC combination with a decorative surface. Total nominal thickness is 4 mil. Supplied with a silicone liner, which protects the clear, pressure-sensitive adhesive, and applied using the same tools and techniques for window films.

Fire Rating:

When applied to glass or plastic surfaces:
 Horizontal Burn (Flame Spread) ASTM D-635 inch Less than 1.0
 UL 94 Rating UL Classification V-O
 Class A 0 -25 Flame Spread Index 0 -450

Installation and Warranty

Installation

Installation should be in accordance with manufacturer's installation instructions.

Warranty

This SOLYX® product will be free from defects in material and manufacture for a period of five (5) years from the date of installation.

See Warranty information for specific details.

Product Distribution and Contact Information

Distribution

SOLYX® Decorative Films are available through qualified Installing Dealers, Distributors or from Decorative Films, LLC.

Samples submitted upon request.

Contact Information

Decorative Films, LLC
 1-888-657-5224
www.decorativefilm.com

Product Description

SOLYX® SXHK-01 Shoji Screen is a white, opaque, rice paper film. An exact representation of Rice Paper and is ideal for obscuring direct visibility while allowing subtle light transmission.

Specifications

Product Code	SXHK-01
Product Family	Patterned Privacy
Film Type	Polyester Fiber & PVC
Adhesive Type	Pressure-sensitive
Usage	Interior
Available Width(s)	36" (914.4mm)
Full Roll Length	54 linear feet (16.5m)
Thickness	4 mil
Visible Light Transmission	10%
UV Transmission	5%
Total Solar Energy Absorbed	23%
U Value	1.75
Shading Coefficient	.65
Total Solar Energy Rejected	78%

Product Construction

Face Film

2 mil Vinyl

Adhesive

Clear, Pressure-sensitive

Release Liner

Silicone

Product Details