

# SOLYX® Glass Finishes

# SOLYX: SXJ-0540 Lines Gradient



# **Product Description**

SOLYX: SXJ-0540 Lines Gradient is a frosted polyester film with a translucent gradient background effect and superimposed with a tall grass pattern. Ideal for direct visibility control.

### **Specifications**

| Product Code                | SXJ-0540                |
|-----------------------------|-------------------------|
| Product Family              | Gradients               |
| Film Type                   | SOLYX iQ Polyester      |
| Adhesive Type               | Pressure-sensitive      |
| Usage                       | Interior or Exterior    |
| Available Height            | 60",71" (or custom)     |
| Full Roll Length            | 100 linear feet (30.5m) |
| Thickness                   | 4mil                    |
| Shading Coefficient         | 0.55                    |
| Visible Light Reflection    | 27%                     |
| Visible Light Transmission  | 75%                     |
| UV Transmission             | 2%                      |
| Total Solar energy Rejected | 38%                     |
|                             |                         |
| Solar Energy Absorbed       | 25%                     |
| Infra-Red Transmission      | 70%                     |
|                             |                         |

# **Product Construction**

Face Film

4 mil SOLYX iQ polyester

**Adhesive** 

Clear, Pressure-sensitive

Release Liner Silicone

### **Product Details**

### **Manufacturer Detail**

SOLYX: SXJ-0540 Lines Gradient is a frosted polyester film with a translucent gradient background effect and superimposed with a tall grass pattern. Ideal for direct visibility control. This film is designed for application to interior glass, single or double pane and exterior facing glass. Made of durable Polyester with a matte printed design, perfect for privacy, decorative or architectural applications. The total nominal thickness is 4 mil (100 micron). Manufactured with a silicone liner, which protects the clear, pressure-sensitive adhesive, and applied using the same tools and techniques for window films.

# **Installation and Warranty**

### Installation

Installation should be in accordance with manufacturer's installation instructions.

### Warranty

This SOLYX® product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details

# **Product Distribution and Contact Information**

### Distribution

**SOLYX® Decorative Films** are available through qualified Installing Dealers, Distributors or from Decorative Films, LLC.

Samples submitted upon request.

# **Contact Information**

Decorative Films, LLC 1-888-657-5224 www.decorativefilm.com