

SOLYX® Glass Finishes

SOLYX: SXJ-0580 Gloss Symmetric Fine Dots Gradient



Product Details

SOLYX: SXJ-0580 Gloss symmetric Fine Dot Gradient is a polyester film with a white translucent dual fading gradient in a small dot design pattern. This film has a **gloss finish** and is ideal for direct visibility control. This film is designed for application to interior glass, single or double pane and exterior facing glass. Made of durable Polyester with a scratch resistant coating, perfect for privacy, decorative or architectural applications. Manufactured with a silicone liner, which protects the clear, pressure-sensitive adhesive, and applied using the same tools and techniques for window films.

Flammability Rating:

When applied to surfaces- glass or plastic sheet:

Horizontal Burn (Flame Spread) ASTM D-635 inch Less than 1.0

UL 94 Rating UL 94 UL Classification V-O

Class A 0 -25 Flame Spread Index 0 -450 Smoke Developed Index

SOLYX Films are suitable for installation onto fire rated glass and will not affect the rating of fire rated glass.

Installation and Warranty

Installation

Installation should be in accordance with manufacturer's installation instructions.

Warranty

This SOLYX® product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details

Product Distribution and Contact Information

Distribution

SOLYX® Decorative Films are available through qualified Installing Dealers, Distributors or from Decorative Films, LLC.

Samples submitted upon request.

Contact Information

Decorative Films, LLC

1-888-657-5224

www.decorativefilm.com

Product Description

SOLYX: SXJ-0580 Gloss Symmetric Fine Dot Gradient is a polyester film with a white translucent dual fading small dot design gradient pattern. Ideal for direct visibility control.

Specifications

Product Code	SXJ-0580
Product Family	Gradients
Film Type	Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior
Available Height	60"
Full Roll Length	100 linear feet (30.5m)
Thickness	2mil
Shading Coefficient	0.55
Visible Light Reflection	27%
Visible Light Transmission	75%
UV Transmission	2%
Total Solar energy Rejected	38%

Solar Energy Absorbed	25%
Infra-Red Transmission	70%

Product Construction

Face Film

2 mil SOLYX polyester

Adhesive

Clear, Pressure-sensitive

Release Liner

Silicone