

## SOLYX® SXP-020 UV AMBER POLYESTER



### PRODUCT DETAIL:

**SOLYX® SXP-020 AMBER POLYESTER FILM** Decorative Privacy Glass Film recommended for application to interior glass. This film is a premium 2.0mil dyed polyester with a scratch resistant surface added. It is perfect semi-privacy and decorative or architectural applications and blue light blocking. Film can be combined with other SXP films to create multiple colors.

### Fire Rating

The product was tested according to ASTM E84 and is classified as Class A, as defined in NFPA 101, Life Safety Code®.

### PRODUCT DESCRIPTION:

**SOLYX® SXP-020 UV AMBER POLYESTER FILM.** Durable, dimensionally stable, transparent, optically clear polyester film. Suitable for Blue Light Blocking.

### Specifications

Product Code	SXP-020 UV Amber
Product Family	Colored Window Films
Film Type	Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior
Available Width(s)	60" (1524mm)
Full Roll Length	100 linear feet
Thickness	2.0mil
Shading Coefficient (%)	.82%
Visible Light Reflectance (%)	9%
Visible Light Transmission (%)	39%
UV Transmission (%)	1%
IR Transmission	90%
Total Solar Energy Rejected	32%
Blue Light Blocking 450-500nm	<10% transmission

### Installation and Warranty

#### Installation

Installation should be in accordance with manufacturer's installation instructions. Installed using the same methods for installing window films.

#### Warranty

This SOLYX® product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See Warranty information for specific details.

### Product Distribution and Contact Information

#### Distribution

**SOLYX® Decorative Films** are available through qualified Installing Dealers, Distributors or from Decorative Films, LLC

Samples submitted upon request.

#### Contact Information

Contact Decorative Films, LLC at 1-888-657-5224 or [www.decorativefilm.com](http://www.decorativefilm.com)

### PRODUCT CONSTRUCTION:

**First Surface – Scratch Resistant Coating**

**Face Film:** 2.0 mil Polyester

**Adhesive:** Clear, permanent pressure-sensitive acrylic.

**Liner :** 1.5 mil Transparent Polyester

